



MOTION™ LE1700 TABLET PC

PRODUCT SPECIFICATIONS



Chassis	<ul style="list-style-type: none"> Polycarbonate - upper bezel Magnesium Alloy - lower bezel 	Batteries	<ul style="list-style-type: none"> Standard Battery <ul style="list-style-type: none"> Lithium-ion battery with 38.5Whr capacity Battery Life: ~3 hours Optional Extended Battery <ul style="list-style-type: none"> Lithium-polymer with 40Whr capacity Combined battery capacity <ul style="list-style-type: none"> Maximum 78.5Whr Battery life: ~6-7 hours
Operating System	<ul style="list-style-type: none"> Microsoft® Windows Vista® Business 	Battery Charging Times	<ul style="list-style-type: none"> Standard Battery only <ul style="list-style-type: none"> 1.5 hours (Tablet PC on/off)³ Standard Battery with Extended Battery attached <ul style="list-style-type: none"> 3.5 hours (Tablet PC on/off)³
Processors/Cache	<ul style="list-style-type: none"> Intel® Core™2 Duo Processor Low Voltage L7400 (4MB of L2 cache, 1.5GHz, 667MHz FSB) Intel® Core™2 Duo Processor Ultra Low Voltage U7500 (2MB of L2 cache, 1.06GHz, 533MHz FSB) 	System Status LEDs	<ul style="list-style-type: none"> Power on/off/stand by Battery status LED
Chipset	<ul style="list-style-type: none"> Intel® 945GM Express 	Control Buttons	<ul style="list-style-type: none"> One 5-way directional control button for navigation One function button, one programmable escape button and two programmable buttons Secure Attention Sequence (SAS) button Wireless on/off button
Display Options	<ul style="list-style-type: none"> 12.1" UltraView SXGA+ display 12.1" UltraView Anywhere SXGA+ display 12.1" View Anywhere XGA display 12.1" XGA display 	AC Adapter	<ul style="list-style-type: none"> 50W universal, 3-pin jack 100-240V 1.5a, 50-60Hz
Graphics	<ul style="list-style-type: none"> Intel® Graphics Media Accelerator 950 Rotation: 0°, 90° 	System Software	<ul style="list-style-type: none"> Motion Dashboard control panel Motion/Softex OmniPass™ Security software Infineon Security Platform Tools Adobe® Acrobat® Reader Windows Journal Sticky Notes Pen/button-based setup utility
Video RAM	<ul style="list-style-type: none"> Maximum 256MB total with Intel Dynamic Video Memory Technology (DVMT) 	Environmental	<ul style="list-style-type: none"> Temperature <ul style="list-style-type: none"> Operation: +5°C to +35°C Storage: -20°C to +60°C Humidity <ul style="list-style-type: none"> Operating humidity: 8% to 80% without condensation Storage humidity: 8% to 90% without condensation Altitude <ul style="list-style-type: none"> Operation: sea level 0 to 10K ft. Storage: sea level 0 to 40K ft.
Audio Controller	<ul style="list-style-type: none"> Intel® High Definition Audio 	Standards	<ul style="list-style-type: none"> ACPI 2.0 compliant
PC Card Controller	<ul style="list-style-type: none"> Industry-standard CardBus controller 	Regulatory	<ul style="list-style-type: none"> AS/NZS 3548:1995 Class B AS/ACIF S042.1 (WCDMA/HSDPA) AS/ACIF S042.3 (WCDMA/HSDPA) AS/ACIF S042.1 (GSM/EDGE) AS/ACIF S042.3 (GSM/EDGE) FCC Part 15 Subpart B Class B FCC Part 15 Subpart C (2.4Ghz) FCC Part 15 Subpart E (5Ghz) FCC Part 22 H (1xRTT/EVDO-0/EVDO-A) FCC Part 24 E (1xRTT/EVDO-0/EVDO-A) FCC OET65 Supplement C (01-01) CAN/CSA ICES-003 Class B CAN/CSA RSS-210 Issue 5 CAN/CSA RSS-132 CAN/CSA RSS-133 CENELEC EN 55022 Class B (CISPR22) CENELEC EN 55024 (CISPR24) CENELEC EN 61000-3-2 CENELEC EN 61000-3-3 ETSI EN 301-893 ETSI EN 300-328-2 ETSI EN 301-489-1 ETSI EN 301-489-7 ETSI EN 301-489-17 ETSI EN 301-489-24 R&TTE (89/336/EEC) & R&TTE (99/5/EC) EN 50392:2004 / IEC 62209-1:2005
System Memory	<ul style="list-style-type: none"> Base RAM: 2GB 667MHz DDR2 memory with Dual Channel memory support Upgradeable to a maximum of 4GB 	System Storage	<ul style="list-style-type: none"> 1.8" Hard Disk Drive (HDD) with 80GB capacity Optional 64GB Solid State Drive (SSD) PCI bus master enhanced IDE Supports Ultra ATA 66/100 4200 RPM
System Storage	<ul style="list-style-type: none"> 1.8" Hard Disk Drive (HDD) with 80GB capacity Optional 64GB Solid State Drive (SSD) PCI bus master enhanced IDE Supports Ultra ATA 66/100 4200 RPM 	Communications	<ul style="list-style-type: none"> Integrated UMTS Unlocked HSDPA 3.6 Mbps Novatel Wireless EU870D Mobile Broadband (optional) Atheros 802.11a/b/g card Intel PRO/Wireless 3945 a/b/g card (optional) Integrated 10/100/1000 Ethernet LAN controller with RJ-45 connector (Gigabit Ethernet) Integrated Bluetooth®
Communications	<ul style="list-style-type: none"> Integrated UMTS Unlocked HSDPA 3.6 Mbps Novatel Wireless EU870D Mobile Broadband (optional) Atheros 802.11a/b/g card Intel PRO/Wireless 3945 a/b/g card (optional) Integrated 10/100/1000 Ethernet LAN controller with RJ-45 connector (Gigabit Ethernet) Integrated Bluetooth® 	Audio	<ul style="list-style-type: none"> Motion Speak Anywhere® technology <ul style="list-style-type: none"> Multi-directional array microphone design intelligently switches between two of the three microphones based on screen orientation Two integrated speakers
Audio	<ul style="list-style-type: none"> Motion Speak Anywhere® technology <ul style="list-style-type: none"> Multi-directional array microphone design intelligently switches between two of the three microphones based on screen orientation Two integrated speakers 	I/O Ports	<ul style="list-style-type: none"> Microphone-in Headphone-out Two USB 2.0 ports DVI-D custom connector IrDA port External VGA port Motion accessory port RJ-45 connector Docking connector DC power in
I/O Ports	<ul style="list-style-type: none"> Microphone-in Headphone-out Two USB 2.0 ports DVI-D custom connector IrDA port External VGA port Motion accessory port RJ-45 connector Docking connector DC power in 	Expansion Card Slots	<ul style="list-style-type: none"> Secure Digital (SD) slot One Type I or Type II PC card slot SIM card slot
Expansion Card Slots	<ul style="list-style-type: none"> Secure Digital (SD) slot One Type I or Type II PC card slot SIM card slot 	Security	<ul style="list-style-type: none"> Integrated Fingerprint Reader TCG Trusted Platform Module (TPM) 1.2 Universal lock slot ComputraceComplete (optional) Motion DataGuard™
Security	<ul style="list-style-type: none"> Integrated Fingerprint Reader TCG Trusted Platform Module (TPM) 1.2 Universal lock slot ComputraceComplete (optional) Motion DataGuard™ 	Dimensions	<ul style="list-style-type: none"> 11.65" x 9.64" x 0.74" - 0.87" (296mm x 245mm x 18.7 - 22mm)
Dimensions	<ul style="list-style-type: none"> 11.65" x 9.64" x 0.74" - 0.87" (296mm x 245mm x 18.7 - 22mm) 	Weight	<ul style="list-style-type: none"> 3.3 lbs. with Standard Battery¹ 4.3 lbs. with Extended Battery²
Weight	<ul style="list-style-type: none"> 3.3 lbs. with Standard Battery¹ 4.3 lbs. with Extended Battery² 	Safety	<ul style="list-style-type: none"> UL, CUL, TUV (EN/IEC 60950-1 A11/2004) EU Directive 2002/95/EC EU Directive 2002/96/EC California Proposition 65
Warranty	<ul style="list-style-type: none"> Standard 1-year warranty Multi-year options available 	Warranty	<ul style="list-style-type: none"> Standard 1-year warranty Multi-year options available

For more information and localized websites, please visit www.MotionComputing.com

¹Weight represents approximate system weight measured with a 38.5Whr battery, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

²Weight represents approximate system weight measured with both the 38.5Whr Standard Battery and a 40Whr Extended Battery attached, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

³Approximate charging time. Validated charging from 5% to 90% with system on or system off.